LISTING OF CLAIMS

- 1-29. (Canceled)
- 30. (Currently Amended) A <u>light transmitting</u> photochromic lens <u>comprising</u> photochromic dyes and having a visible colored appearance, the photochromic lens <u>further</u> comprising a multi-layer thin film coating applied on <u>an</u> outer surface thereof, the multi-layer thin film coating comprising a plurality of dielectric layers, wherein the film coating reflects an amount less than about 15% of spectral ultraviolet radiation in a range between 315 and 400 nm and reflects an amount equal to or greater than about 10% of light in the visible spectrum in a range between 410 and 800 nm so that the lens exhibits the visible colored appearance.
- 31. (Previously Presented) The lens of claim 30, wherein the colored appearance comprises a mirror like appearance.
- 32. (Previously Presented) The lens of claim 30, wherein the colored appearance comprises a white silver like appearance.
- 33. (Previously Presented) The lens of claim 30, wherein the multi-layer thin film coating reflects less than 6% of spectral ultraviolet radiation.
- 34. (Previously Presented) The lens of claim 30, wherein the plurality of dielectric layers comprises SiO₂ layers.
- 35. (Previously Presented) The lens of claim 30, wherein the plurality of dielectric layers comprises TiO₂ layers.

- 36. (Previously Presented) The lens of claim 30, wherein the plurality of dielectric layers are arranged to alternate low and high refractive indices.
- 37. (Previously Presented) The lens of claim 30, wherein the plurality of dielectric layers comprises ZrO₂ layers.
- 38. (Previously Presented) The lens of claim 30, wherein the plurality of dielectric layers comprises twelve layers.
- 39. (Previously Presented) The lens of claim 38, wherein the multi-layer thin film coating comprises a twelve layer arrangement comprising alternating TiO₂ and SiO₂ layers.
- 40. (Previously Presented) The lens of claim 38, wherein the multi-layer thin film coating comprises a twelve layer arrangement comprising TiO₂, SiO₂ and ZrO₂ layers.
 - 41. (Canceled)
- 42. (Previously Presented) The lens of claim 30, wherein the plurality of dielectric layers comprises up to 100 layers.
- 43. (Currently Amended) The lens of claim 30, the lens having <u>a photochromic range</u> an activation value of greater than about 25%.
- 44. (Currently Amended) The lens of claim 30, the lens having a photochromic range an activation value of greater than about 40%.
- 45. (Currently Amended) The lens of claim 30, the lens having a photochromic range an activation value of greater than about 90%.

- 46. (Currently Amended) The lens of claim 30, the lens having a photochromic range an activation value of greater than about 297% 97%.
- 47. (Currently Amended) The lens of claim 30, the lens having <u>a photochromic range</u> an activation value of approximately the activation value of the uncoated photochromic lens.
- 48. (Previously Presented) The lens of claim 39, wherein the dielectric layers are selected and arranged in a sequence: TiO2, SiO2, TiO2, TiO2, SiO2, TiO2, SiO2, TiO2, TiO2, TiO2, SiO2, TiO2, TiO2,
- 49. (Previously Presented) The lens of claim 40, wherein the dielectric layers are selected and arranged in a sequence: TiO2, SiO2, TiO2, SiO2, ZrO₂, SiO2, TiO2, SiO2, TiO2, SiO2, ZrO₂, SiO2, Si
- 50. (Previously Presented) The lens of claim 30, wherein the lens is a sunglass lens.
- 51. (Currently Amended) A method of creating a <u>light transmitting</u> colored photochromic lens <u>comprising photochromic dyes</u>, the method comprising <u>forming a photochromic lens part and applying a plurality of dielectric layers onto the outer surface of a photochromic lens <u>part</u> wherein the plurality of dielectric layers collectively reflect an amount less than about 15% of spectral ultraviolet radiation in a range between 315 and 400 nm and reflect an amount equal to or greater than about 10% of light in the visible spectrum in a range between 410 and 800 nm so that the lens exhibits a visible colored appearance.</u>

- 52. (Previously Presented) The method of claim 51, further comprising applying a twelve layer arrangement comprising alternating TiO₂ and SiO₂ layers.
- 53. (Previously Presented) The method of claim 52, further comprising applying twelve layers of TiO2 and SiO2 on the photochromic lens in a sequence: TiO2, SiO2, in order to obtain a silver mirror like appearance.
- 54. (Previously Presented) The method of claim 51, further comprising applying a twelve layer arrangement comprising TiO₂, SiO₂ and ZrO₂ layers.
- 55. (Previously Presented) The method of claim 54, further comprising applying twelve layers of TiO2, SiO2 and ZrO2 on the photochromic lens in a sequence: TiO2, SiO2, TiO2, SiO2, ZrO2, SiO2, TiO2, SiO2, TiO2, SiO2, ZrO2, SiO2, in order to obtain a white silver like appearance.
- 56. (New) The method of claim 51, wherein the forming the photochromic lens part includes:

forming a lens part and imbibing one or more photochromic dyes onto a surface of the lens part; or

dissolving one or more photochromic dyes in a mass of polymer and forming the lens part therefrom; or

forming a lens part and coating the lens part with one or more photochromic dyes onto a surface of the lens part.

57. (New) A photochromic sunglass lens, ophthalmic lens, visor or mask having a visible colored appearance, comprising:

a photochromic lens part constructed and shaped to be worn proximate a person's eyes,

the lens part having an inner surface facing the eyes and an outer surface facing outward away from the eyes,

the lens part further comprising one or more photochromic dyes; and a light-transmitting multi-layer thin film coating applied on the outer surface of the lens part, the multi-layer thin film coating comprising a plurality of dielectric layers,

wherein the film coating transmits an amount greater than about 15% of spectral ultraviolet radiation in a range between 315 and 400 nm to the lens part,

the film coating reflecting an amount equal to or greater than about 10% of light in the visible spectrum in a range between 410 and 800 nm so that the sunglass lens, ophthalmic lens, visor or mask exhibits the visible colored appearance;

wherein the sunglass, ophthalmic lens, visor or mask transmits light therethrough.

- 58. (New) The sunglass lens, ophthalmic lens, visor or mask of claim 57, wherein the photochromic dyes in the lens part impart a photochromic range to the sunglass lens, ophthalmic lens, visor or mask.
 - 59. (New) A photochromic screen having a visible colored appearance, comprising: a photochromic lens part,

the lens part having an inner surface and an outer surface, the lens part further comprising one or more photochromic dyes; and

a light-transmitting multi-layer thin film coating applied on the outer surface of the lens part, the multi-layer thin film coating comprising a plurality of dielectric layers,

wherein the film coating transmits an amount greater than about 15% of spectral ultraviolet radiation in a range between 315 and 400 nm to the lens part,

the film coating reflecting an amount equal to or greater than about 10% of light in the visible spectrum in a range between 410 and 800 nm so that the screen exhibits the visible colored appearance;

wherein the screen transmits light therethrough.

60. (New) The screen of claim 59, wherein the photochromic dyes in the lens part impart a photochromic range to the screen.